



OPTIONS

Colours:

Yellow, Black or Grey

Bespoke:

Any RAL / BS colour*

Dimensions:

Manufactured on a 1mm thick GRP sheet
600 mm x 150 mm
Custom sizes to order*

Additional Options:

Custom cross section sizes available*
Choice of colour*
Choice of grit size*

* Minimum order quantity may apply.

SPECIFICATION

Cleat & resin coatings:

High quality isophthalic polyesters

Grit:

Refined aluminium oxide

Hardness:

9.5 moh / 2200 knoop diamond
Industrial(grade 16, medium/coarse)

Suitable traffic:

Foot, lift truck, vehicular

Can be fixed to:

Concrete, metal, wood, ceramics,
plastics

Fixing methods:

Sealant/adhesive, or peel & stick, high-tack modified acrylic self-adhesive version

Product is water-jet cut for best appearance

BENEFITS

- > highly effective anti-slip safety surface
- > long lasting & durable
- > suitable for all environments, exterior or interior
- > refined, extra-hard aluminium oxide granules give superior performance & wear characteristics (compared to common quartz grit finishes)
- > far outlasts anti slip tapes, floor paints & coatings
- > little or no maintenance requirement
- > rapid & easy installation – choice of either self-adhesive or dispensed adhesive to suit any existing surface
- > resistant to wide range of chemicals (full details available)
- > full range RAL & BS colours available to order*
- > Equality Act compliant products available
- > conforms to UK Building Regulations
- > easily cleanable
- > rapid delivery: typically 3-5 days for standard items & 10 days for bespoke products*

*subject to order type & size

APPLICATIONS

Typical applications:

- ramps
- steps
- walkways
- wooden/steel access structures

DESCRIPTION

A tough GRP tread or step cover measuring 600 x 150mm. A coating combination of premium quality aluminium oxide & resin components, make up a highly effective Anti-slip product that will withstand the rigours of all industrial & commercial environments.

A preferred choice over tapes and paints, they offer an almost permanent solution to slip hazards.

The product is also offered with an optional peel & stick self-adhesive backing for easy installation. Both types can be fixed to all substrate types in sound, clean condition.

The overall height of the product means no additional trip hazard is presented, with no requirement for chamfered edges.

Available in a choice of colours, the product is boxed prior to delivery.