



## OPTIONS

### Colours available:

#### Standard:

Yellow, Black or Grey

#### Bespoke:

Any RAL / BS colour

### Dimensions:

Manufactured on a 1mm thick GRP sheet  
Standard sheet dimensions: 3000 mm x 1220 mm\*

### Additional Options:

- Resin finished highlighted edges
- Choice of colour
- Choice of grit size
- Water jet cutting of intricate designs/shapes/logos or strips
- Cut to size prior to delivery
- Full range of fasteners & adhesives for all on-site scenarios

\*Custom sizes to order.

Minimum order quantity may apply.  
Please contact us for further information.

## SPECIFICATION

### Sheet & resin coatings:

High quality isophthalic polyesters

### Grit:

Refined aluminium oxide

### Hardness:

9.5 moh / 2200 knoop diamond

### Suitable traffic:

Foot, lift truck, vehicular

### Can be fixed to:

Concrete, metal, wood, ceramics, plastics

### Fixing methods:

Sealant/adhesive only, or in combination with panhead screw or clout nail

## BENEFITS

- > highly effective anti-slip safety surface
- > long lasting & durable
- > suitable for all environments, exterior or interior
- > refined, extra-hard aluminium oxide granules give superior performance & wear characteristics (compared to common quartz grit finishes)
- > choice of grit grade – barefoot (grade 40, extra-fine), pedestrian (grade 24, fine), industrial (grade 16, medium/coarse) & offshore (grade 12, extra coarse)
- > far outlasts anti slip tapes, floor paints & coatings
- > little or no maintenance requirement
- > light weight sheets/profiles
- > rapid & easy installation – choice of fasteners/adhesives to suit any existing surface
- > resistant to wide range of chemicals (full details available)
- > full range RAL & BS colours available to order
- > Equality Act compliant products available
- > conforms to UK Building Regulations
- > easily cleanable
- > rapid delivery: typically 3-5 days for standard items & 10 days for bespoke products\*
- > free cutting service\*

\*subject to order type & size

## APPLICATIONS

### Typical applications:

- ramps
- platforms
- walkways
- bridges

## DESCRIPTION

A nominally 1mm tough GRP sheet coated in a combination of premium quality aluminium oxide & resin components make up a highly effective Anti-slip product that will withstand the rigours of all industrial & commercial environments.

The preferred choice over tapes and paints, it offers an almost permanent solution to slip hazards. Extensively used in food factories it can be laid and fixed using a single part adhesive/sealant to bond and seal the edges, preventing the ingress of moisture & microbes.

The overall height of the product means no additional trip hazard is presented, with no requirement for chamfered edges.

Sheets may be cut to specification for immediate installation.

Designed to be fixed with adhesive to all substrate types in sound condition, Low Profile Anti-slip can be laid onto undulating surfaces and walkways where Standard thickness sheeting may not be suitable.