



OPTIONS

Std Colours:

Yellow

Bespoke:

Any RAL / BS colour

Dimensions:

Manufactured on a nominally 2mm thick GRP profile with integral downstand

Stocked profiles:

Length: 3200 mm
Depth x downstand: 70 mm x 30 mm |
55 mm x 55 mm (EA Compliant)

Bespoke profiles:

Length : 3000 mm
Depth x downstand: (min-max) : 25-150
mm x 25-150 mm

Additional Options:

Chamfered & resin finished edges
Pre-drilled fixing points
Choice of colour
Choice of grit size*
Cut to exact sizes prior to delivery
Full range of fasteners & adhesives for all on-site scenarios

* Minimum order quantities may apply.
Please contact us for further information

SPECIFICATION

Profile & resin coatings:

High quality isophthalic polyesters

Grit:

Refined aluminium oxide

Hardness:

9.5 moh / 2200 knoop diamond

Suitable traffic:

Foot

Can be fixed to:

Chequerplate, concrete, metal, wood, ceramics, open mesh grating

Fixing methods:

Sealant/adhesive in combination with countersunk/panhead screws or self-drilling screws

BENEFITS

- > highly effective anti-slip safety surface
- > long lasting & durable
- > suitable for all environments, exterior or interior
- > refined, extra-hard aluminium oxide granules give superior performance & wear characteristics (compared to common quartz grit finishes), industrial (grade 16, medium/coarse)
- > far outlasts anti slip tapes, floor paints & coatings
- > little or no maintenance requirement
- > light weight profiles add insignificant load to existing structures
- > rapid & easy installation - choice of fasteners/adhesives to suit any existing surface
- > resistant to a wide range of chemicals (full details available)
- > full range of RAL & BS colours available to order
- > Equality Act compliant products available
- > conforms to UK Building Regulations
- > easily cleanable
- > rapid delivery: typically 3-5 days for stocked items & 10 days for bespoke products*
- > free cutting service*

*subject to order type & size

APPLICATIONS

Typical applications:

- staircases
- steps

DESCRIPTION

A nominally 2mm thick, tough GRP profiled cover, coated in a combination of premium quality aluminium oxide & resin components gives the Stair Nosing product a highly effective and durable Anti-slip surface that will withstand the rigours of all industrial & commercial environments. Designed specifically to reduce the risk of slipping on step edges, they are the preferred choice over tapes and paints, offering an almost permanent solution to slip hazards. The products can be laid and fixed using a combination of adhesive/sealant and fasteners to effectively fix, bond and seal the edges, preventing any ingress of moisture.

In conformance with parts M1/M2 of the Building Regulations and Equality Act legislation (formerly Disability Discrimination Act) the nosings are made apparent by means of a permanently contrasting material on both the tread and riser. Also the surfaces are firm, durable and slip-resistant.

The product also features a chamfered back edge to reduce the possibility of a trip hazard.

Designed to be fixed to all substrate types with a choice of fixing methods available at despatch.

To accommodate all requirements, stocks of standard product types are always available, complemented by rapid, bespoke made solutions direct from our UK manufacturing facilities.