



SWING GATE & SLIDING GATE

The **Swing Gate & Sliding Gate** are designed to be compatible with the **Handrail** product range and allow controlled access/egress into and out from a designated walkway.

For added safety where a route has been defined, it is important to provide delineation using a gate rather than leave a gap in the barrier run where a pedestrian may then inadvertently walk into an unsafe condition.

The **Swing Gate** incorporates a high quality self-closing double action hinge mechanism allowing bi-directional access. Both **Swing & Sliding Gates** are available with a range of standard openings and can be supplied as single units or in pairs. Narrower gates are available to special order.

Sliding Gates are fitted with a small hard wearing nylon floor wheel ensuring the gate is supported during travel and provides a consistently smooth operation. In addition, both types of gates can be optionally fitted with a tower bolt so they may be secured in either an open or closed position.

In loading bays or enclosures where a **Swing Gate** in an open position would present an obstruction to traffic movement, or be inconvenient for traffic access, the **Sliding Gate** is an ideal solution as it opens into an adjacent section of standard pedestrian barrier, the length of which is determined by the gate opening.

The gate and barrier sections are supplied as a preassembled unit.

Component parts are manufactured from a highly durable synthetic polymer derivative. The material has great resilience, yet is elastic in nature and absorbs the energy from impacts, before returning to its original shape.

The gates have been designed and developed to comply with relevant safety standards and regulations.

PRODUCT SPECIFICATION:

BENEFITS:

- Rapid & easy installation - reduced labour costs & disruption
- Maximum protection
- Attractive aesthetics
- No welding needed for assembly
- No painting
- Little or no maintenance/repair costs
- Highly durable
- Chemical resistant
- Long lifetime
- 100% recyclable
- Tested to EU norms

APPLICATIONS:

- Controlled access/egress of pedestrians into and out from a designated walkway

SPECIFICATIONS:

- **Gate rail:**
Synthetic polymer derivative
- **Base plates (built in):**
Steel or stainless steel (coated)

OPTIONS:

Standard colours available:

- Black/Yellow
- **Options:** Grey, Yellow/Black, Yellow, Black/Luminescent

Sizes:

- Standard module:
L 1000mm, 1500mm or 2000mm x H 1100mm
- Custom lengths:
all sizes up to 2000mm

Options:

- Safety signs
- Stainless steel version

PLEASE CALL:

01757 212 744

to discuss your specific requirements with a member of our experienced team.